



NOTE
 MATERIAL
 HOUSING:PBT+30%G/F,BLUE UL94V-0.
 SHELL:BRASS C2680-H.
 CONTACT:PHOSPHOR BRONZE C2680/C5191
 CONTACT PLATE WITH GOLD 15U" PLATE
 SHELL:NICKEL 80U"(MIN) PLATE
 DIELECTRIC WITHSTANDING VOLTAGE:100V(AC).
 CONTACT RESISTANCE:50M Ω MAX
 INSULATION RESISTANCE:100M Ω MIN
 OPERATING TEMPERATURE: -55°C~105°C.
 PART NO. DESCRIPTION:

12 1-09 1 1 N X XX 02
 PLATING GOLD: _____ STANDARD
 A=1u" B=3u" _____ HOUSING COLOR:
 C=5u" D=10u" _____ 05=BLUE -----
 E=15u" F=30u" O=0.5u"

10/05/22	ING		NEW DWG		AO
DATE	DR.BY	ECN.NO.	DESCRIPTION		MARK VER.
-TOLERANCES- UNLESS OTHERWISE SPECIFIED 公差参考表			  TITLE: USB 3.0 A 公焊線式三件式		
X.X	± 0.30	X.X'	± 3.00	APPD:	PRODUCT NO: 121-0911NE0502
X.XX	± 0.20	X.XX'	± 1.00	CHECK:	DATE SCALE UNIT TYPE PAGE
X.XXX	± 0.10	X.XXX'	± 0.05	DRAW:	2010.05.22 1:1 mm Z 1/1